

# ELECTRA IW1002 BE

## Product Data Sheet



The IW1002 Be's sophisticated design enables it to compete with any high-end loudspeaker thanks to its pure Beryllium inverted dome tweeter and its latest generation 'W' cone woofer loaded with integrated sealed volume. The highest-fidelity in invisible version.



### Key features

- True compact alternative to the traditional high-end 2-way loudspeaker
- Easy and quick installation
- Optional mounting kit (for walls under construction)
- Speaker drivers developed and manufactured in France by Focal
- Ready-to-paint grille

Type	2-way In-Wall sealed speaker
Drivers	6 1/2" (16.5cm) 'W' midbass 1 1/4" (27mm) Be inverted dome tweeter
Frequency response ( $\pm 3$ dB)	60H-40kHz
Sensitivity (2.83V/1m)	88dB
Nominal impedance	8 $\Omega$
Recommended amplifier power	25-150W
Tweeter adjustment	-3dB / 0dB / +3dB
Crossover frequency	2,600Hz
Frame size: - with grille - without grille	16 3/4" x 12 1/8" - 0 3/16" thick (425x308mm - 4.5mm thick) 16 1/3" x 11 3/4" - 0 1/16" thick (415x298mm - 1.5mm thick)
Cut-out dimensions (HxW)	14 15/16" x 10 3/8" (379x262mm)
Depth from wall	3 7/8" (99mm)
Net weight	14.1lbs (6.4kg)

