## BT-AKKUPOLE

## DESCRIPTION

Stylish battery-powered 4x 5Watt LED-lighting pole with wireless DMX, perfect to light up buffets, presentation counters, etc.

## **FEATURES**

- Stylishly designed battery-powered lighting pole with great autonomy.
- The perfect tool for illuminating buffets, presentation counters, etc.
- Equipped with 4 pivoting 5 watt 25° LED projectors (3000K & CRI>90)
- The sturdy swivel arm with projectors can be set in 6 fixed positions.
- Lightning fast assembly/disassembly without any tools.
- Sturdy construction quality with adjustable height for frequent and versatile use in rental jobs.
- The supplied heavy base (45x37cm) ensures very high stability, even at maximum height.
- Equipped with magnetic filter holders for the use of all kinds of filters:
  - CTO/CTB filters: adjust CCT to e.g. 4000K, 2700K, ...
  - Color filters: choose any color imaginable
  - Frost filters: adjust beam angle
- Clear and very easy user interface.
- 3 touch buttons and clear LCD screen with information about remaining battery time.
- Multiple operating modes:
  - Built-in wireless DMX receiver (with XLR output: can serve as W-DMX receiver)
  - Wired DMX control via XLR in/out (1 dimming channel)
  - Simple manual operation on the base.
- High capacity lithium batteries (288Wh) for extended autonomy (>14.5 hours at 100% output).
- Internal processor-controlled battery charger with IP65 PowerKon in/output.
- Works perfectly on mains power as well (batteries are recharged during use)
- Professional flight case (120x60cm) optionally available for transport of 4 complete sets.









www.briteq-lighting.com | https://www.facebook.com/Briteq

## TECHNICAL SPECIFICATIONS

Architectural, Commercial, Stage & **General: Application** 

General: Weight (kg) 25

**General: Powerinput** AC 100 - 240V, 50/60Hz

**General: Energy Label General: Power consumption W** 69 **General: Color** black **General: Display** LCD **General: IP rating** indoor

**Control: Modes** standalone, manual, DMX M/S

**Control: manual Control: Master/Slave** Yes **Control: SMART-DMX** No **Control: Standalone** fixed **Control: programmable** No **Control: upgradable software** No **Control: maximum DMX channels** 1 **Light: lamp socket** none Light: lamp LED

Light: min. color temperature (K) 3200 Light : max. color temperature (K) 3200 Light: CRI 90 **Light: mix colors** No **Light**: min. beam angle (°) 25 **Light**: max. beam angle (°) 50 Light: min. refresh rate (kHz) No Light: max. refresh rate (kHz) No

3 pin XLR, TRUE1 powerCON, **Connections: input** 

wireless DMX

3 pin XLR, TRUE1 powerCON,

**Connections: output** wireless DMX **Brand** BRITEQ **EA NCode** 5420025651622









