

# SUB 708-AS II

## ACTIVE SUBWOOFER

### DESCRIPTION

Thanks to the powerful 18" woofer, with 3.0" voice coil, and the 1400-Watt amplifier, the SUB 708-AS II is the perfect tool to increase the low end performance of a portable PA system, both in terms of output and frequency extension. Thanks to the built-in digital stereo crossover (DSP) with adjustable crossover frequency it can be easily and quickly set up as a satellite speaker system. The SUB 708-AS II perfectly match 12" or 15" satellite speakers. The SUB 708-AS II is the ideal companion subwoofer the RCF ART 3, ART 7 or D-Line Series.



### FEATURES

- 1400 Watt Digital Amplifier
- 18" Woofer, bass reflex housing
- Stereo crossover
- Switchable crossover frequencies
- Phase-reverse switch
- Electronic equalization, soft limiter and protection
- Stereo XLR input, Stereo XLR signal output

## TECHNICAL SPECIFICATIONS

<b>Acoustical specifications</b>	Frequency Response:	35 Hz ÷ 120 Hz
	Max SPL @ 1m:	133 dB
<b>Transducers</b>	Woofers:	18", 3.0" v.c
<b>Input/Output section</b>	Input signal:	bal/unbal
	Input connectors:	XLR
	Output connectors:	XLR
	Input sensitivity:	-2 dBu/+4 dBu
<b>Processor section</b>	Hi-Pass Frequencies:	110 Hz
	Low-Pass Frequencies:	80 Hz
	Protections:	Thermal, RMS
	Limiter:	Soft Limiter
	Controls:	Volume, EQ, Phase, Xover
<b>Power section</b>	Total Power:	1400 W Peak, 700 W RMS
	Low frequencies:	1400 W Peak, 700 W RMS
	Cooling:	Convection
	Connections:	VDE
<b>Standard compliance</b>	CE marking:	Yes
<b>Physical specifications</b>	Cabinet/Case Material:	Baltic birch plywood
	Handles:	2 side
	Pole mount/Cap:	Yes
	Grille:	Steel
	Color:	Black
<b>Size</b>	Height:	665 mm / 26.18 inches
	Width:	505 mm / 19.88 inches
	Depth:	700 mm / 27.56 inches
	Weight:	39 kg / 85.98 lbs
<b>Shipping informations</b>	Package Height:	702 mm / 27.64 inches
	Package Width:	557 mm / 21.93 inches
	Package Depth:	752 mm / 29.61 inches
	Package Weight:	44 kg / 97 lbs

## PART NUMBER

- |                   |                   |
|-------------------|-------------------|
| • <b>13000458</b> | • <b>13000457</b> |
| SUB 708-AS II     | SUB 708-AS II     |
| 115V              | 220-240V          |
| EAN 8024530012960 | EAN 8024530012908 |

# SUB 708-AS II



