

BT-THEATRE 100MZ

B06029

DESCRIPTION

Powerful 100W LED theater Fresnel with exceptional photometric / price ratio and light output comparable to 1kW halogen theatre projectors!

FEATURES

- Powerful 100W LED theater Fresnel with CCT= 3000K
- The light output can be easily compared to that of traditional 1kW halogen theatre projectors!
- Exceptional photometric / price performance: CRI / Ra >96, TLCI >97, CQS >94, Rf >92, Rg >97 !
- Manual beam angle adjustment: 15° ~ 45° (field angle: 22° ~ 60°)
- Color frame for use of color filters and eight-leaf barndoor included.
- No more heavy and expensive dimmer packs needed!
- Very silent operation: temperature controlled, low noise cooling fan.
- LCD-display to navigate easily through the setup menu!
- Manual or DMX-controlled: 4 different channel modes (8bit & 16bit dimming) for maximum flexibility.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE ! (Briteq® code: B04645)
- Flicker free TV-recordings thanks to 1.2kHz LED refresh rate!
- Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
- Selectable lamp behavior: halogen lamp (slow) or led (fast).
- Four dimmer curves: linear, square, inverse square, S-curve.
- In case of DMX failure, you can choose between manual, blackout and freeze mode.
- RDM-functionality for easy remote setup & monitoring: DMX addressing, channel mode, temperature, ...
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3 & 5pin DMX in/outputs + ProLock in/outputs for easy daisy chaining.







www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2020 by BEGLEC NV. All rights reserved.

TECHNICAL SPECIFICATIONS

General : Application	Theatre
General : Dimensions (cm)	See drawing
General : Weight (kg)	7.2
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	105
General : Color	black
General : Display	LCD
General : Fixation	M12
General : IP rating	indoor
Control : Modes	standalone, manual
Control : manual	Yes
Control : Master/Slave	No
Control : SMART-DMX	No
Control : Standalone	fixed
Control : programmable	No
Control : upgradable software	Yes
Control : maximum DMX channels	4
Light : lamp socket	none
Light : Lux	2630 (@ 5m beam 16°)
Light : lamp	COB
Light : min. color temperature (K)	3000
Light : max. color temperature (K)	3000
Light : CRI	95
Light : colors	Warm white
Light : mix colors	No
Light : functions	manual focus, manual zoom
Light : min. beam angle (°)	15
Light : max. beam angle (°)	45
Light : min. refresh rate (kHz)	1.2
Light : max. refresh rate (kHz)	1.2
Connections : input	3 pin XLR, 5 pin XLR, PowerCon®, usb
Connections : output	3 pin XLR, 5 pin XLR, PowerCon®, usb
Brand	BRITEQ
EANCode	5420025660297



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2020 by BEGLEC NV. All rights reserved.