

CMX20T

8" two-way loudspeaker, white



CMX20T two-way built-in loudspeaker produces a warm and deep sound ideal for speech and music. The CMX20T loudspeaker has an 8" enforced polypropylene woofer and 1" tweeter. Due to this enforced woofer, the loudspeaker has a very low distortion! It makes the CMX20T very suitable for the distribution of microphone calls and background music at a higher volume level.

The housing is made of high quality ABS. The woofer is made out of enforced polypropylene with a rubber edge, what makes it moisture-proof. The aluminium grille makes CMX20T humidity proof and suitable for use in bathrooms and kitchens.

In 16 ohms use, you can connect up to 4 loudspeakers in parallel on each channel of a standard 4 ohms amplifier. For 100 volt use, the CMX20T is equipped with a high-quality 20 watts 100 volt transformer with several power tappings (20 -10-5-2.5 watts).

This loudspeaker is easy to install, due to its simple, quick mounting system with only 3 screws. These screws are hidden behind the loudspeaker grill, what gives the loudspeaker a modern and striking design. From 12 pieces on, the CMX20T loudspeakers can be painted optionally in any other RAL colour (REF: PAINT-CM).

TECHNICAL SPECIFICATIONS

outside diameter in mm	244	depth in mm	87
cutout in mm	223	loudspeaker system	2-way
woofer size in inch	8	woofer cone material	polypropylene
tweeter size in inch	1	mounting system	3 screws
colour	white / black	100V transformer power taps in	20 - 10 - 5 - 2.5
impedance in ohms	16	watts	
·		low impedance power in watts	100
SPL 1W/1m in dB	88	CDI 4 to -ID	100
frequency response in Hz	50 - 20K	max SPL 1m in dB	108
rrequericy response in riz	30 ZOK	main construction material	ABS plastic
grille main material	aluminium		·
applicable low impedance Yes	V	IP rating	54
	Yes	applicable in 100V	Yes
		applicable III 1000	162



MORE PICTURES

