



## SMARTTAPE6020-5

**SKU:** H11253

Tri-color pixel LED tape  
60 LEDs/meter - IP20 - 5 V

The new WS2813 LED allows operation over the entire tape even if an LED fails.

**Color:**



---

**Categories:** [Tapes](#), [Pixel tapes](#)

## ADDITIONAL INFORMATION

### General characteristics:

- Trichromatic ribbon 60 LEDs/m (300 LEDs for 5 m)
- LED WS2813
- Opening : 120°.
- Power requirement: 14 W/m (70 W for 5 m)
- Required voltage: 5 V DC
- Color variation: Requires a compatible converter
- IP20: Not resistant to water splashes

### Dimensions:

- Length: 5m roll
- Thickness: 3 mm
- Width: 10 mm
- Can be cut every 17 mm

### Accessories :

- 4-wire input cable (Data +, Backup, Ground, +V) pre-mounted
- 4-wire output cable (Data +, Backup, Ground, +V) pre-mounted
- Full length 3M self-adhesive tape



## ADDITIONAL INFORMATION

<b>Input voltage</b>	5 V
<b>Number of LEDs/m</b>	60 LEDs
<b>On-mode power</b>	14 W/m
<b>Efficacité totale (lm/W)</b>	18
<b>Protection class</b>	IP20
<b>LED type</b>	WS2813
<b>Luminous flux (lm/m)</b>	272
<b>CRI</b>	39
<b>Chromaticity coordinate (x)</b>	0.2138
<b>Chromaticity coordinate (y)</b>	0.2339
<b>Lighting technology used</b>	LED
<b>Non-directional or directional</b>	Non-directional
<b>Angle de faisceau (°)</b>	120°
<b>Mains or non-mains</b>	Non-mains
<b>Connected light source (CLS)</b>	No
<b>Colour-tunable</b>	Yes
<b>Standby power</b>	
<b>Height (mm)</b>	3
<b>Width (mm)</b>	10
<b>Split length</b>	17 mm