



CONNECT SERIES TOUCH DATASHEET

The LEA Connect Series Touch is designed to be an elegant volume and source selection solution for LEA Connect Series amplifier installations. The Connect Series Touch is easily programmed via the amplifier's WebUI software and can control and group multiple amplifier channels allowing endless possibilities for system volume and source selection.

Key Features

- Full color touch screen with rotary encoder
- Programmable via the Connect Series WebUI software
- Group volume control up to 100 LEA Connect Series amplifier channels
- Group source select up to 65 LEA Connect Series amplifier channels
- Multiple Connect Series Touch can be used on the same network
- PoE powered for easy one cable installation
- Works with US and UK/EU single gang wall boxes
- Available in white or black

Models	Color	Black LEA CS Touch - BLK	White LEA CS Touch - WHT
Control & Network	Connect Series Amplifier Control	The Connect Series Touch works in conjunction with all LEA Connect Series amplifiers. To use the Connect Series Touch, you must have an LEA Connect Series amplifier on the same network	
	Multi-Zone Control	Control up to 100 single channel zones across multiple amplifiers from one Connect Series Touch	
	Group Zone Control	Ability to group up to 100 channels on one control from the Connect Series Touch	
	Programmable Functions	Group Volume Control - Ability to control up to 100 individual channel zones or one control for 100 channel zones grouped together Volume Subgroup Control - Control the volume level of a specific zone within a group volume control Group Source Select - Recall amplifier input sources on up to 65 channels grouped together	
	Software	WebUI based, SharkWare support coming soon. *Must have an LEA Connect Series amplifier on the network to configure Connect Series Touch	
	Multi-Device	Multiple Connect Series Touch can be used on the same network	
	Physical Controls	Color touch screen with continuous rotary control	
	Display Resolution	240 x 320px, full RGB	
	Network Connectivity	RJ45. DHCP only. Static IP coming soon with firmware update. Communicates via UDP on ports 7076 and 7077	
	3 rd Party Control	Not currently supported	
Cloud	Not currently supported		
Operation	Power Requirements	PoE power only. Compatible with PoE, PoE+, and PoE++	
	PoE Voltage Range	Operates from 44V to 57V PoE voltage	
	Temperature	Storage: -5°C to 70° C - Operating: 0°C to 50° C	
	PoE Power Consumption	3.5W maximum load	
Physical Spec	Exterior Construction	Black Black anodized semi-matte aluminum	White White painted gloss finish aluminum
	Product Dimensions	Product - Height: 4.4in / 112mm, Depth: 1in / 25mm, Width: 3.2in / 80mm Shipping - Height: 7in / 178mm, Depth: 2in / 51mm, Width: 5 1/2in / 140mm	
	Mounting	Mounts to U.S. single gang box or UK/EU single gang box	
	Mounting Dimensions	US Mount Top and bottom holes: 3.281in spacing	UK/EU Mount Left and right holes: 2.36in / 60mm spacing
	Weight	Product: 0.5lbs / 220g Shipping: 0.6lbs / 280g	

LEA Professional reserves the right to make any necessary changes to the specification. The LEA Professional Warranty is six years from date of purchase and product registration in the United States. Internationally, the warranty is five years from date of purchase from an LEA Professional Authorized Distributor.

