



东莞常禾电子有限公司

EVERVICTORY ELECTRONIC COMPANY LIMITED

PRODUCTION SPECIFICATION

页次： 版次：A/1

CUSTOMER (顾客)	METRO	DESCRIPTION (描述)	25φ TW
CUSTOMER MODEL (顾客型号)		SAMPLE ES ORDER NO. (样)	
ORIGINAL MODEL (本厂型号)	PL8 TW	FINISHED DATE/EDITION (完成时间)	2015/01/30

PRODUCTION SPEC.

NO.	ITEM(项目)	SPECIFICATION(规格)	TEST CONDITION(测试条件)
1	Effective IMP. (额定阻抗)	8 Ω ±15%	20°C At / HZ 1V
2	R.DC. (直流阻抗)	6.0 Ω ±10%	20°C
3	Resonant Freq. (最低共振频率)	/ HZ ±20%	Free space without baffle
4	SPL (灵敏度)	MEAN VALUE AT 88 ±3dB	AT V ON CALCULATED FROM 1M MEASUREMENT <input type="checkbox"/> DASS <input checked="" type="checkbox"/> LMS <input type="checkbox"/> MLSSA
5	Rated freq.range (额定频率范围)	2K ~ 20 KHz	±10dB(1M/1W)
6	Distortion (失真率)	Less than %	At W Hz
7	Qts (总的品质因数)		
8	Rated power (额定输入功率)	3 W	
9	Max power (最大输入功率)	/ W	
10	Flux density (磁通密度)	GAUSS ±10%	
11	Operation (动作)	Must be normal	/ V / ~ / Hz
12	Sweep test (受音音)	Must be normal	3 V 2K ~ 20 KHz
13	Magnet (磁铁)	* * Material <input checked="" type="checkbox"/> Ferrite; / Oz <input type="checkbox"/> Neodymium	
14	Voice Coil (音)	25 φ <input checked="" type="checkbox"/> ASV <input type="checkbox"/> BASV <input type="checkbox"/> KSV <input type="checkbox"/> TSV <input type="checkbox"/> NSV <input type="checkbox"/> PESV <input type="checkbox"/> AL <input type="checkbox"/> Titanium	
15	Cone (膜体)	<input type="checkbox"/> PAPER <input type="checkbox"/> PP <input type="checkbox"/> Injection <input type="checkbox"/> Glass fiber <input type="checkbox"/> Carber fiber <input type="checkbox"/> Kevler	
16	Tweeter Material (高音膜片材质)	<input type="checkbox"/> Mylar <input type="checkbox"/> PEI <input checked="" type="checkbox"/> Silk <input type="checkbox"/> Cloth <input type="checkbox"/> Titanium	
17	Transformer Spec (变压器规格)	V~ V/ W W W	

RELIABILITY TEST SPEC.(可靠性测试规格)

NO.	ITEM (项目)	TEST CONDITION(测试条件)
1	Power test (功率测试)	Noise V hrs
2	Heat & humidity (耐)	°C %RH hrs °C %RH hrs
3	UV-Resistance (抗紫外线测试)	hrs
4	Vibration test (振动测试)	
5	Drop test (落地测试)	
6		

Prepare: 洪伟群 Check: 洪伟群 Approval: Customer approval:

DR-QR-33.A/2