BEAMSPOT1-DMX FC

DESCRIPTION

Stylish DMX-controlled 15W RGBW single beam projector, equipped with a very narrow 4° lens making it a very powerful tool for all kinds of applications.

FEATURES

- This compact, stylish 15W RGBW single beam projector is equipped with a very narrow 4° lens making it a very powerful tool for all kinds of applications: perfect for all kinds of effects on stage but also for simply illuminating mirror balls etc.
- Thanks to the included 10° & 45° filters this beauty can also be used for discotheques, exhibition booths, ... (perfect to light up small objects and small tables)
- Six different DMX-modes: from 4 to 7 channels.
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- The OLED-display assures easy navigation in the different setup menus.
- TV-Studio ready: no cooling fans and flicker free 1200Hz LED refresh rate.
- Selectable lamp behavior: halogen lamp (slow) or led (fast)
- Four dimmer curves: linear, square, inverse square, S-curve
 In case of DMX failure you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- White balance adjustment to perfectly match the colors of several projectors.
- Default factory settings + user settings can be saved/loaded.
- An IR-Remote is optionally available
- 3pin DMX in/outputs and $\text{Neutrik}^{\texttt{®}}$ PowerCON $^{\texttt{®}}$ in/outputs for easy daisy chaining.






www.briteq-lighting.com | https://www.facebook.com/Briteq


Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2015 by BEGLEC NV. All rights reserved.

SPECIFICATIONS

General : Application General : Dimensions (cm) General : Weight (kg) **General : Powerinput General : Energy Label** General : Power consumption W **General : Color General : Display General : Fixation General : IP rating Control : manual Control : Master/Slave** Control : DMX M/S **Control : Standalone Control : Type included remote Control : optional remote Control : programmable Control : upgradable software Control : maximum DMX channels** Light : lamp socket Light : Lux Light : lumen Light : lamp Light : min. color temperature (K) Light : max. color temperature (K) Light : CRI Light : colors Light : mix colors Light : fixed gobos Light : rotating gobos Light : focus Light : zoom Light : iris Light : prism (# facets + rotating y/n) Light : min. beam angle (°) Light : max. beam angle (°) **Connections : input Connections : output Connections : XLR 3 pin Connections : XLR 5 pin Connections : Power Conn. Connections : midi Connections : usb Connections : wifi Connections : bluetooth Connections : artnet Connections : rdm** Brand EANCode Discontinued

Commercial lighting, DJ & Club, Stage & Rental 17,2 x 19,6 x 12,5 cm 1.23 AC 100 - 240V, 50/60Hz No 15 black No M10 indoor Yes Yes No automatic, sound, fixed IR-2 No Yes 7 none 1820 Lux at 5m (beam angle 4°) 275 LED Red, Green, Blue, White, RGBW Yes None Manual No 4 45 3 pin XLR, powercon, rdm 3 pin XLR, powercon Yes No Yes No No No No No Yes BRITEQ





LUX (full on)		454	450	11400				5050			2845			1820		
BEAMSPOT1-DMX FC							-									
										16						
BEAM: 4°		L.	GI	ΕT	RE	SE	A R	CF								
DISTANCE (m) BEAM Ø (cm)		1			2 14			3			4 28			5 35		
BEAM Ø (CM)		1				4		21			20			30		





www.briteq-lighting.com | https://www.facebook.com/Briteq

5420025649575

No

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2015 by BEGLEC NV. All rights reserved.