BT-THEATRE 60FC (BLACK)

DESCRIPTION

Stylish 60Watt full color LED theater spot with manual $10^\circ \sim 50^\circ$ zoom.

FEATURES

- Stylish 60Watt full color LED theater spot with manual 10° \sim 50° zoom.
- Thanks to its attractive looks this projector is perfect for use in clubs, exhibition booths, rental, ...
- Four-leaf barndoor included
- No more heavy and expensive dimmer packs needed!
- Create any color thanks to the 60W RGBW LED.
- Low noise, temperature controlled, cooling fan
- Extruded black anodized aluminium housing with strong bracket
- LCD-display to select different working modes:
 - Standalone (master) Mode : set dimmer + strobe (if needed)
 - Master/slave mode: connect several projectors together, the first projector controls the others.
 - DMX-controlled: 6 different channel modes for maximum flexibility.
- Selectable lamp behavior: halogen lamp (slow) or led (fast)
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure you can choose between blackout and freeze mode.
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- Lock function to avoid unwanted altering of the settings.
- White balance adjustment to perfectly match the colors of several projectors.
- Default factory settings + user settings can be saved/loaded.
- 3pin DMX in/outputs and fixed 1m power cord with standard mains plug (CEE 7/7)








www.briteq-lighting.com | https://www.facebook.com/Briteq


Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2015 by BEGLEC NV. All rights reserved.

SPECIFICATIONS

General : Application General : Dimensions (cm) General : Weight (kg) **General : Powerinput General : Energy Label** General : Power consumption W **General : Color General : Display General : Fixation General : IP rating Control : manual Control : Master/Slave** Control : DMX M/S **Control : Standalone Control : Type included remote Control : optional remote Control : programmable Control : upgradable software Control : maximum DMX channels** Light : lamp socket Light : Lux Light : lumen Light : lamp Light : min. color temperature (K) Light : max. color temperature (K) Light : CRI Light : colors Light : mix colors Light : fixed gobos Light : rotating gobos Light : focus Light : zoom Light : iris Light : prism (# facets + rotating y/n) **Light : frost filter** Light : min. beam angle (°) Light : max. beam angle (°) **Connections : input Connections : output Connections : XLR 3 pin Connections : XLR 5 pin Connections : Power Conn. Connections : midi Connections : usb Connections : wifi Connections : bluetooth Connections : artnet Connections : rdm** Brand EANCode Discontinued No

Architectural, Commercial lighting, Theatre 24,1 x 25,1 x 19,5 cm 3.63 AC 100 - 240V, 50/60Hz No 62 black LCD optional standard clamp indoor Yes Yes No automatic, sound, fixed No Yes 7 none 330 lux at 5m and 10°, 77 lux at 5m and 40° COB RGBW Yes None Manual No No 10 50 3 pin XLR, rdm 3 pin XLR Yes No No No No no No No Yes BRITEQ 5420025660150





LUX (full on)	8220	2060	920	515	330
BT-THEATRE 60TC					
BEAM: 10°	LIGHT	RESEA	RCH		
DISTANCE (m) BEAM Ø (cm)	1 17	2 35	3 52	4 70	5 87
	17	55	JZ	10	07
LUX (full on)	1910	480	215	120	77
BT-THEATRE 60TC					
BEAM: 40°	LIGHT	RESEA	R C. P		
DISTANCE (m)	1	2	3	4	5 364
BEAM Ø (cm)	73	146	218	291	364

YOUR DEALER



www.briteq-lighting.com | https://www.facebook.com/Briteq

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2015 by BEGLEC NV. All rights reserved.