# LDP-COLORBAR 24FC

#### DESCRIPTION

Powerful IP65 LED projector (length: 96cm) equipped with 24pcs 4W RGBW leds. The projector is divided in 4 independent sections.

### **FEATURES**

- Powerful indoor / outdoor IP65 LED projector equipped for typical "wall wash" applications.
- Excellent light output and perfect color mixing thanks to 4Watt RGBW LEDs and high quality optics.
- Available in 2 versions:
  - LDP-COLORBAR 12FC: 48cm long enclosure, equipped with 12 leds, divided into 2 sections.
  - LDP-COLORBAR 24FC: 96cm long enclosure, equipped with 24 leds, divided into 4 sections.
- Elegant, extruded aluminum housing finished with tempered glass cover.
- The discretely designed bracket can be easily adjusted in any position.
- The included barndoor hides the LEDs and thus reduces unwanted glare.
- Optimal thermal management for long lifespan and easy maintenance
- Internal power supply and DMX / LED-driver electronics for easy installation.
- Waterproof input and output connectors allow the user to link up to 16pcs of LDP-COLORBAR 12/24FC.
- Perfect for use in hotels, clubs, shops, homes, ...
- Excellent built-in programs for wonderful, ever changing, light shows.
- Completely silent operation, thanks to natural convection cooling system.
- Alphanumeric OLED-display and waterproof touch keys to select different options of the setup menu.
- Works in standalone, master/slave or can be selected by DMX: fading colors, static colors / chases
- Both models can be daisy chained and used together in master/slave
- Full DMX control with different channel modes: from 3ch up to 10ch (2 sections) or 20ch (4 sections)
- Adaptable lamp behavior thanks to seamless dimmer speed control.
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure, you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Special waterproof DMX in/outputs with adapter cables to XLR for maximum compatibility
- Equipped with a special GORE ® vent to prevent moisture and condensation inside the projector.
- Optional cables available for easy, waterproof daisy chaining (LDP-Powercable & Signal link cable)









www.briteq-lighting.com | https://www.facebook.com/Briteq

### SPECIFICATIONS

General: Application Architectural, DJ & Club, Stage &

Rental

**General : Dimensions (cm)**  $96 \times 5.6 \times 11.4/13.5$ 

**General: Weight (kg)** 5.1

**General: Powerinput** AC 100 - 240V, 50/60Hz

General : Energy LabelNoGeneral : Power consumption W85General : Colorwhite

General: Color white
General: Display OLED
General: Fixation M10
General: IP rating outdoor
Control: manual Yes
Control: Master/Slave Yes
Control: SMART-DMX Yes

**Control : Standalone** automatic, fixed

Control : programmable No
Control : upgradable software Yes
Control : maximum DMX channels 20
Light : lamp socket none
Light : lamp

**Light : colors**Red, Green, Blue, White, RGB,

Light: mix colors

Light: mix colors

Light: iris

No

Light: frost filter

No

Light: min. beam angle (°)

Light: max. beam angle (°)

Light: min. refresh rate (kHz)

Light: max. refresh rate (kHz)

3.6


**Connections : input**3 pin XLR, ip-powerlink connector **Connections : output**3 pin XLR, ip-powerlink connector

**Brand** BRITE Q **EA NCode** 5420025651462

**Discontinued** No

12FC = 481 (24FC = 960)

12FC = 299 (24FC = 557)









## www.briteq-lighting.com | https://www.facebook.com/Briteq