BT-COLORAY 18FCR

DESCRIPTION

Outdoor projector with 18x8W RGBW leds, 20° beam angle and Neutrik TRUE1 Powercon and 5P XLR connectors and IP-fan cooling.

FEATURES

- This stylish 18x8W RGBW projector with a 20° beam angle is a very powerful tool for all kinds of events (stage, TV-show, exhibition boots, architectural lighting,...)
- IP65 rating
- Three different DMX-modes: 4, 6 and 7 channels.
- RDM-functionality for easy remote setup: DMX addressing, channel mode. . . .
- The LCD-display assures easy navigation in the different setup menus.
- TV-Studio ready: flicker free 1200Hz LED refresh rate.
- Selectable lamp behavior: halogen lamp (slow) or led (fast)
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure you can choose between blackout and freeze mode
- Lock function to avoid unwanted altering of the settings.
- White balance adjustment to perfectly match the colors of several projectors.
- Default factory settings + user settings can be saved/loaded.
- 5pin DMX in/outputs and Neutrik[®] TRUE1 PowerCON[®] in/outputs for easy daisy chaining.
- IP-Fan cooling for longer LED life.









www.briteq-lighting.com | https://www.facebook.com/Briteq

SPECIFICATIONS

General: ApplicationArchitectural, Stage & Rental,
Theatre

Theatre 5.28

General : Weight (kg) General : Powerinput5.28

AC 100 - 240V, 50/60Hz

General : Energy Label No **General : Color** black

General : Display touchscreen

General : Fixation optional omega bracket

General: IP rating outdoor
Control: manual Yes
Control: Master/Slave Yes
Control: SMART-DMX No

Control : Standalone automatic, fixed

Control : programmable No
Control : upgradable software Yes
Control : maximum DMX channels
Light : lamp socket Light : lamp
LED
Light : CRI 72

Light : colors Red, Green, Blue, White, RGBW

Light: mix colors

Light: focus

No

Light: zoom

No

Light: iris

No

Light: min. beam angle (°)

Light: max. beam angle (°)

Light: min. refresh rate (kHz)


Light: max. refresh rate (kHz)


1.2

Connections : input5 pin XLR, TRUE1 powerCON **Connections : output**5 pin XLR, TRUE1 powerCON

Brand BRITEQ

EA NCode 5420025655125 **Discontinued** No





LUX (full on) 19777	4944	2197	1236	791	549
BT-COLORAY 18FCR					
BEAM: 20°					
DISTANCE (m) 1	2	3	4	5	6
BEAM Ø (cm) 39	78	117	156	194	233

YOUR DEALER



www.briteq-lighting.com | https://www.facebook.com/Briteq